



a: O = open loop; S = Strain Gage Sensor

b: D = D-Sub 15 pin connector; L = Lemosa; P = Pigtail

Product	Stroke	Length L
T2a-b00003	3mrad	33,5mm
T2a-b00006	6mrad	53,5mm

nanoFAKTUR
Piezotechnologie + Nanopositionierung

FREI-MASSTOLERANZ
STANDARD TOLERANCE
DIN ISO 2768 - f

MAßSTAB SCALE
2:1

OBERFLÄCHE TREATMENT -
WERKSTOFF / MATERIAL
Alu / Invar / Stainless steel

AUSGABE	ÄNDERUNG	DATUM	NAME
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

DATUM	NAME
KONSTR. 03.03.2017	KPo
GEZ. 03.03.2017	KPo
GEPR. -	-

BEZEICHNUNG / TITLE
Kippplattform / Tip-tilt unit

AUSGABE	ÄNDERUNG	DATUM	NAME
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

All information provided in this drawing is to be considered confidential, proprietary and secret information. It is intended only for the use of the individual or entity to whom it is sent. Individual or entity agrees to not disseminate or copy this information to anyone other than originally specified without the written consent of nanoFaktur GmbH, VS-Villingen.
www.nFaktur.com, info@nFaktur.com

ARTIKEL-ID / ITEM-NO.	VERSION	GÜLTIG BIS
T2a-b0000c	-	-
DOKUMENT-ID / DOCUMENT-NO.	VERSION	GÜLTIG BIS
X	-	-
ABGELEITET V. -	NACHFOLGER F. -	-